

Richpeace Automatic Large Hopper Spreading Machine

RPSM-NM-1-1000X1800-C-N300-NA-1P220



Machine Features

- 1. The large hopper device meets the load-bearing requirements of 0-300kgs fabric roll (diameter less than 1m).
- 2. On LCD touch screen, spreading length, number of layers, speed and spreading mode can be set freely.
- 3. Equipped with remote control, it can remotely control the operation including start, stop, feed and retract within 30m.
- 4. Supplied with automatic edge matching function and layer counting function.

Application

Polar fleece, denim, non-woven fabrics, composite materials, etc.





- 5. With the convenient fabric loading structure, one worker can complete the feeding work, and it can also be equipped with automatic fabric loading device to further reduce the labor intensity.
- 6. During emergency stop, the spread fabric will not be dragged and deformed.
- 7. The multi-stage distribution structure ensures the smoothness of the spreading.
- 8.If the power is cut off during working, the original setting information is still saved after power on, and the spreading can continue.
- 9. All components are supplied by international famous brands to ensure the stability and lifespan of the machine.





Parameters

Spreading Width	1.8m	2.2m		2.5m		3.2m	
Weight after installation	750kgs	900k	900kgs)kgs	1500kgs	
Fabric Roll weight	≤300kgs Work		Workin	ng speed		≤100m/min	
Roll diameter	≤100cm	≤100cm Tota		power	3kw		
Spreading Height	≤28cm		Vol	tage	2	220V, 50Hz	

Machine standard device



Large hopper device Meet the load-bearing requirements of 0-300kgs fabric rolls ($\Phi \le 1$ m).



Walking encoder Make sure that the head travels the same distance each time according to the setting.



Intelligent adjustable cutter device The blade is easy to install and remove, and the built-in sharpening function improves cutting efficiency.



Safety protection inductor The machine will stop automatically to ensure personal safety by sensing human signals within 0.5m around the machine.



Intelligent touch screen operation International PLC control system, stable performance, easy maintenance.



Automatic edge alignment sensor The fabric edge sensor adopts the infrared diffuse reflection technology of international famous brands, and its sensitivity is further improved.

Machine optional devices





Antistatic Device Auto Fabric Loading Device



Zigzag Device



Operator Platform



Electronic Guide Track

TIANJIN RICHPEACE AI CO., LIMITED

Add: No.6 Baozhong Road, Baodi Economic Development Zone, Tianjin City, 301800 China

Tel: +86-22-22533456 Fax: +86-22-22530075 Email: sales@richpeace.com

